



➤ TMC-7 DSP/TMC-6 DSP

Color Interlaced Scan CCD




- *1/2" interline transfer CCD*
- *High performance digital signal processing (DSP)*
- *768 (H) x 494 (V) resolution (NTSC)*
- *752 (H) x 582 (V) resolution (PAL)*
- *High sensitivity complementary color filter*
- *Y/C (S-Video) and RGB output (TMC-7DSP only)*
- *1/60 to 1/10,000 sec. programmable shutter, and auto shutter*
- *RS-232C external control for gain, white balance, and other functions*
- *External sync (HD, VD sync) capability*




Specifications for TMC-7DSP/TMC-6DSP

Specifications	TMC-7DSP	TMC-6DSP
Sensor	1/2" interlaced scan interline transfer CCD	
	ICX418AKL	ICX419AKL
Active pixels	768 (H) x 494 (V)	752 (H) x 582 (V)
Cell size	8.4 μm x 9.8 μm	8.6 μm x 8.3 μm
Color filter	Cy, Ye, Mg, G complementary color filter	
Scanning	2:1 interlaced, field mode scanning	
Synchronization	Internal sync; int sync/ext auto switch with HD/VD-input	
TV resolution	460 x 400 TV lines	450 x 450 TV lines
S/N ratio	>50 dB (AGC off)	
Sensitivity	2.0 lux f=1.4 (AGC on)	
Video output	1.0 Vp-p at 75 Ω (NTSC and PAL) 1.0 Vp-p with sync; Chroma = 285 mV at 75 Ω (Y/C or S-VHS) 714m Vp-p w/o sync, Sync 285mV at 75 Ω (TMC-7DSP)	
Color balance	Through-the-lens auto white balance; memory (std) or auto-tracking (opt) and manual hue adjustment	
AGC	Max 32 dB AGC, on-off switchable, manual gain control	
Gamma	0.45 (factory standard); 1.0 (programmable)	
Lens mount	C-mount	
Power	12V DC, 280 mA	
Operating temperature	-10° C to 50° C	
Vibration	7 Grms (10 Hz to 2000 Hz) Random	
Shock	70 G, 11 ms, half-sine	
Dimensions (H x W x L)	32 mm x 42 mm x 133 mm	
Weight	210 g (without tripod)	


Dimensions




Connector Pin-outs




Shutter Mode Switch



Spectral Response



Remote Head



Ordering Information

Camera	
Lead Processing	TMC-7DSP (NTSC), TMC-6DSP (PAL)
RoHS Compliant	RMC-7DSP (NTSC), RMC-6DSP (PAL)
Optional Accessories (MUST BE ORDERED SEPARATELY)	
Power Cable	12P-02, external sync
Power Supply	external sync 12VDC, 500mA
External Control	Manual shutter speed
RGB Cable	CBL-2R-7D (TMC-7DSP only)
RS-232 Cable	RS-232C-9

Europe, Middle East & Africa
Phone +45 4457 8888
Fax +45 4491 8880

Asia Pacific
Phone +81 45 440 0154
Fax +81 45 440 0166

Americas
Phone (Toll-Free) 1 800 445 5444
Phone +1 408 383 0300



See the possibilities

Visit our web site on www.jai.com

Company and product names mentioned in this datasheet are trademarks or registered trademarks of their respective owners. IAI-A-S cannot be held responsible for any technical or typographical errors and reserves the right to make changes to products and documentation without prior notification.

71-0077 Rev. C.05.16.2007