



❖ TMC-73M / TMC-63M

Color Interlaced Scan CCD




- *High efficiency 1/3" interline transfer CCD with micro lenses*
- *768H x 494V resolution (NTSC)*
- *752H x 582V resolution (PAL)*
- *Small size, rugged construction*
- *Shutter from 1/60 to 1/10,000 sec.*
- *Selectable white balance, auto-shutter and AGC*
- *External adjustments for gain, hue, chroma, and other functions*
- *Low light sensitivity of 5 lux at f/1.4*
- *OEM boardsets available*




Specifications for TMC-73M/TMC-63M

Specifications	TMC-73M	TMC-63M
Sensor	1/3" interlaced scan IT CCD	
	ICX408AK-6	ICX409AK-6
Active pixels	768 (H) x 494 (V)	752 (H) x 582 (V)
Cell size	6.35 μm x 7.4 μm	7.35 μm x 7.4 μm
Color filter	Cy, Ye, Mg, G complementary color filter	
Scanning	2.1 interlace, field mode scanning	
	525 lines, 59.54 Hz	625 lines, 50 Hz
Synchronization	Internal sync only	
	fH=15.734 KHz fV=59.95 Hz	fH=15.625 KHz fV=50.00 Hz
TV resolution	460 (H) x 400 (V) TVL	450 (H) x 450 (V) TVL
S/N ratio	>50 dB (AGC off)	
Sensitivity	5.0 lux f=1.4 (AGC ON)	
Video output	VBS= 1.0 Vp-p at 75 Ω (NTSC & PAL) Y=1.0 Vp-p with sync, C= 285 mV at 75 Ω	
Color balance	Manual white balance (selectable)	
AGC	Max. 32 dB AGC, on-off switchable, manual gain control	
Gamma	0.45	
Lens mount	CS-mount	
Power	12V DC, 190 mA	
Auto Iris connector	Internal wiring only, galvanometric iris driver and iris video output	
Operating temperature	-10° C to 50° C (-30° C to +65° C extended temp optional)	
Vibration	7 Grms (10 Hz to 2000 Hz) Random	
Shock	70 G, 11 ms, half-sine	
Dimensions	40 mm dia. x 73 mm	
Weight	120 g (without tripod)	


Dimensions




Spectral Response



Connector Pin-out



Switches



Switches
 Auto/MAN ... Auto-shutter on/off switch. Manual control by Do, D1, D2
 AGC/MGC ... AGC on/off switch. Manual control by serial input 55/32 White balance at 5500°K/3200°K

External control mode (optional)
 12 bit serial D/A is built-in. It controls 8 bits of data and 4 bits of address for
 1. Manual Gain, 2. Iris level control for galvanometric lens, 3. Chroma level,
 4. R-Y hue control, 5. B-Y hue control, 6. Spare for Ext. control mode. Set EXT
 cont (#%) to Low and apply serial data. Clock and Load to #7, 8 and 9 pins.
 Consult JAI for details.

Ordering Information

Camera	
Lead Processing	TMC-73M (NTSC), TMC-63M (PAL)
RoHS Compliant	RMC-73M (NTSC), RMC-63M (PAL)
Optional Accessories (MUST BE ORDERED SEPARATELY)	
Power Supply	12VDC, 300mA
Power Cable	12P-02 for NTSC/PAL and Y/C KC-10 for NTSC/PAL only

Europe, Middle East & Africa
 Phone +45 4457 8888
 Fax +45 4491 8880

Asia Pacific
 Phone +81 45 440 0154
 Fax +81 45 440 0166

Americas
 Phone (Toll-Free) 1 800 445 5444
 Phone +1 408 383 0300

Visit our web site on www.jai.com See the possibilities



Company and product names mentioned in this datasheet are trademarks or registered trademarks of their respective owners. JAI-A-S cannot be held responsible for any technical or typographical errors and reserves the right to make changes to products and documentation without prior notification.

71-0008 Rev. C.05.16.2007